

FOX S3

ÖQË3M453NÉÇ \ \ [D

CE UNI EN ISO 20345:2012 S3 SRC ESD



Tæcæ|æçæ|cä}^}Äc~|çææ|vä}^, MICROËc^&@ c^}ä•cêÄ}æ} *æ•cæÄ}æ\•~•Ä
1,8-2,0 mm. S^} *ê•êÄ^Äæ•cæçæÄ^}äc^ä•\ [@cäæÉ
X~ [|ä^|äccêä}Ä@^} *äccêçêêÄæÄ^} |^c^}^} \^•cêçêêÄ { æc^|æææ|ææÉ
Ú^@ { ^êÉ^Ä^ç^•cä|c []æcc^Ä|ê]]êÉ
HsMG-B' A9H5@@-HCB' ?9B?s"



J5FJ5GGI C>5 200J polymeerinen **_c a dçg]]hh** (täyttää vaatimukset EN 12568)

J s@=DC<->5 nauaanastumissuoja joustava komposiittikangas (täyttää vaatimukset EN 12568)

POHJA 3MOVE kolmikerroksinen, antistaattinen polyuretaanipohja. Kestää hyvin hydrolyysia (ISO 5423:92), hiilivetyjä ja hankausta, vaimentaa iskuja ja on erittäin pitävä **SRC**

ANTI TORSION pohjan kiertojäykiste tukee jalkaa epätasaisella alustalla

MEMORY POHJALLINEN vaihdettava pohjallinen, johon kolmen materiaalin yhdistelmä tuo extramukavuutta. Pehmeä, jalan mukaan muotoutuva Memory-vahto vähentää jalkoihin kohdistuvaa painetta, suojaten kantapään ja päkiän aluetta rasitukselta. Hengittävä, anatominen, iskuja vaimentava, antistaattinen ja antibakteerinen.

ESD Täyttää standardin IEC 61340-4-3:2017 (IEC 61340-5-1:2016) vaatimukset (Elektroniikkalaitteiden staattiselta sähköltä suojaamisen yleiset vaatimukset)


Koot 36-47 Kengän paino koko 42 gr. 510

*Paino on laskettu ilman nauhoja ja pohjallista

CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



3Move is a revolutionary line: thanks to the curved design of its sole, it guarantees the right posture while walking for all the shoe lifelongs. Another characteristic is the heel relief area that allows a perfect weight cushioning. These peculiarities permit an extreme naturalness in walking that, at the end of the day, ensures a huge saving of energy and fatigue. 3Move belongs to the 3D generation. This shoe has 3 different layers with different densities in order to increase Comfort, Anti-slipping and foot Stability. All this line is equipped with the antitorsion insert in order to ensure an additional support at every step.

ANTI SLIPPING SOLE

ANTISLIPPING TEST RESULTS



	request	results
SRA ceramic+NALS	HEEL >= 0,28 FLAT >= 0,32	0,38 0,40
SRB steel+glycerine	HEEL >= 0,13 FLAT >= 0,18	0,27 0,34

PLUS



ANTI TORSION

The usage of the anti-torsion shank is finalized to give to the shoe extreme stability on every ground. Mostly indicated for the building sector, where the risks caused by uneven and wet grounds are higher, this technology is very useful for people working on ladders (painters, windows' cleaners, bricklayers) as it increases the stability in the central part of the plant, the mostly standed area on the ladder. It limits the heel stress and helps plant arch and ankle.



3D TRIPLA DENSITA' INIETTATA

3D is a revolutionary certified technology that offers the only shoe with three different layers of polyurethane injected. The most external section, with hard mix, offers the maximum resistance for the surface contact and perfect SRC performances. The middle part, with a softer mix, assures comfort when walking. The higher section, next to the upper, guarantees better stability to the foot. Three densities and the combination of three colors are the special characteristics of this new shoes generation.